

CE250A

KVM Extender

Control your system from both a local console and a remote console up to 150 meters away




Enhanced Video Quality




CE250AR
(Remote unit)

CE250AL
(Local unit)

The new CE250A outperforms the CE250 in almost every area! The following table compares their features:

	CE250	CE250A
Picture		
Video Resolution	1280 x 1024	1280 x 1024
Video Quality	Fair	Superior
ESD Protection	8000V	8000V
Surge Protection	No	2000V
Non-Powered	No	Local Unit
Rack Mountable	No	Yes
Housing	Plastic	Metal

Diagram



- Console PS/2
- Computers PS/2
- Extension 150 meters

- NEW OS Support Vista
- Non-Powered for CE250A Local Unit

Features

- Cat 5e cable to connect the Local and Remote Units -up to 150 m apart
- Dual console operation - control your system from both the local and remote PS/2 keyboard, mouse and monitor consoles
- Pushbutton selection of the active console
- High resolution video -up to 1280 x 1024 @ 60 Hz
- Supports VGA, SVGA, and Multisync monitors -local monitor supports DDC; DDC2; DDC2B
- Supports Microsoft Intellimouse and the scrolling wheel on most mice.
- Automatic gain control automatically adjusts signal strength to compensate for distance
- Built-in 8KV ESD protection and 2KV surge protection
- Local unit takes its power from the computer – external power is only required when the power from the local computer/computers in the KVM installation is insufficient
- Rack Mountable
- Built-in ASIC for greater reliability and compatibility

Specifications

Function		CE250AL	CE250AR
Console Selection		1 x Pushbutton	
Connectors	Console	1 x 6-pin Mini-DIN Female (Purple)	
	Video	1 x HDB-15 Female (Blue)	
	Mouse	1 x 6-pin Mini-DIN Female (Green)	
	KVM Port	1 x SPHD-15 Female	
Power		1 x DC Jack	
Unit to Unit		1 x RJ-45	
LEDs	Local	1 (Green)	N/A
	Remote	1 (Green)	N/A
	Power	N/A	1 (Green)
	On Line	N/A	1 (Green)
Emulation		Keyboard/Mouse PS/2	
Video		1280 x 1024 @ 60Hz (150 m) DDC; DDC2; DDC2B*	
Power Consumption		DC 5.0V: 1.25W (max.)	
Environment	Operating Temp.	0-50°C	
	Storage Temp.	-20-60°C	
	Humidity	0-80% RH	
Physical Properties	Housing	Metal;	
	Weight	0.33 kg	0.32 kg
	Dimensions (L x W x H)	12.50 x 8.15 x 2.50 cm	

* The specifications and pictures are subject to change without notice.