



Datasheet

Single Plug Adapter EU



Item No.
1.100100

Description
Single Plug Adapter EU

Colour
white

EAN
7640167560011

Customs tariff code
8536.6990



Technical details:

Safety proofed:	IEC 60884, LVD EN 60950, DEKRA, UL
Input voltage:	110 - 250V
Max. load:	16A
Power rating:	100V - 1600W / 250V - 4000W
3 Pol:	Yes
Earthed:	Yes
USB Output:	No
USB protection:	Not necessary

Logistic details:

	length mm	width mm	high mm	gram
Product	58	58	45	75
PU				
Box 1	64	64	80	90
Master				
20	330	140	185	1900
Pallet				
4000	1200	800	1800	kg 380

INPUT

AUSTRALIA/CHINA




2-pole



3-pole

ITALY



3-pole

SWITZERLAND



3-pole

UK




2-pole




3-pole

USA



2-pole



3-pole

EUROPE



2-pole


OUTPUT

EU



Plug type:

F



designed and engineered in Switzerland



Datasheet

Single Plug Adapter EU with USB



Item No.	Description	Colour	EAN	Customs tariff code
1.100110	Single Plug Adapter EU with USB	white	7640167560028	8536.6990



Technical details:


Safety proofed:	IEC 60884, LVD EN 60950, DEKRA, UL
Input voltage:	110 - 250V
Max. load:	16A
Power rating:	100V - 1600W / 250V - 4000W
3 Pol:	Yes
Earthed:	Yes
USB Output:	5V - 2.1Ah
USB protection:	Overload & short circuit

Logistic details:


	length mm	width mm	high mm	gram
Product	58	58	45	75
PU Box 1	64	64	80	103
Master 20	330	140	185	2200
Pallet 4000	1200	800	1800	kg 440

INPUT

AUSTRALIA/CHINA




ITALY




SWITZERLAND



UK



USA




EUROPE



OUTPUT EU WITH USB



Plug type: **F**



designed and engineered in Switzerland



Datasheet

Single Plug Adapter UK



Item No.
1.100120

Description
Single Plug Adapter UK

Colour
white

EAN
7640167560035

Customs tariff code
8536.6990



Technical details:

Safety proofed:	IEC 60884, LVD EN 60950, DEKRA, UL
Input voltage:	110 - 250V
Max. load:	16A
Power rating:	100V - 1600W / 250V - 4000W
3 Pol:	Yes
Earthed:	Yes
USB Output:	No
USB protection:	Not necessary

Logistic details:

	length mm	width mm	high mm	gram
Product	58	58	45	75
PU Box 1	64	64	80	90
Master 20	330	140	185	1900
Pallet 4000	1200	800	1800	kg 380

INPUT

AUSTRALIA/CHINA




2-pole



3-pole

ITALY



3-pole

SWITZERLAND



3-pole

UK




2-pole




3-pole

USA



2-pole



3-pole

EUROPE



2-pole


OUTPUT

UK



Plug type:

G



designed and engineered in Switzerland



Datasheet

Single Plug Adapter UK with USB



Item No.	Description	Colour	EAN	Customs tariff code
1.100130	Single Plug Adapter UK with USB	white	7640167560042	8536.6990



Technical details:


Safety proofed:	IEC 60884, LVD EN 60950, DEKRA, UL
Input voltage:	110 - 250V
Max. load:	16A
Power rating:	100V - 1600W / 250V - 4000W
3 Pol:	Yes
Earthed:	Yes
USB Output:	5V - 2.1Ah
USB protection:	Overload & short circuit

Logistic details:


	length mm	width mm	high mm	gram
Product	58	58	45	75
PU Box 1	64	64	80	103
Master 20	330	140	185	2200
Pallet 4000	1200	800	1800	kg 440

INPUT

AUSTRALIA/CHINA




ITALY




SWITZERLAND




UK



USA




EUROPE



OUTPUT UK WITH USB



Plug type: **G**



designed and engineered in Switzerland



Datasheet

Single Plug Adapter US



Item No.
1.100140

Description
Single Plug Adapter US

Colour
white

EAN
7640167560059

Customs tariff code
8536.6990



Technical details:

Safety proofed:	IEC 60884, LVD EN 60950, DEKRA, UL
Input voltage:	110 - 250V
Max. load:	16A
Power rating:	100V - 1600W / 250V - 4000W
3 Pol:	Yes
Earthed:	Yes
USB Output:	No
USB protection:	Not necessary

Logistic details:

	length mm	width mm	high mm	gram
Product	58	58	45	75
PU Box 1	64	64	80	90
Master 20	330	140	185	1900
Pallet 4000	1200	800	1800	kg 380

INPUT

AUSTRALIA/CHINA




2-pole



3-pole

ITALY



3-pole

SWITZERLAND



3-pole

UK




2-pole




3-pole

USA



2-pole



3-pole

EUROPE



2-pole

OUTPUT

US



Plug type: **B**



designed and engineered in Switzerland



Datasheet

Single Plug Adapter US with USB



Item No.	Description	Colour	EAN	Customs tariff code
1.100150	Single Plug Adapter US with USB	white	7640167560066	8536.6990



Technical details:


Safety proofed:	IEC 60884, LVD EN 60950, DEKRA, UL
Input voltage:	110 - 250V
Max. load:	16A
Power rating:	100V - 1600W / 250V - 4000W
3 Pol:	Yes
Earthed:	Yes
USB Output:	5V - 2.1Ah
USB protection:	Overload & short circuit

Logistic details:


	length mm	width mm	high mm	gram
Product	58	58	45	75
PU Box 1	64	64	80	103
Master 20	330	140	185	2200
Pallet 4000	1200	800	1800	kg 440

INPUT

AUSTRALIA/CHINA




ITALY




SWITZERLAND



UK



USA




EUROPE



OUTPUT US WITH USB



Plug type: **B**



designed and engineered in Switzerland



Datasheet

Single Plug Adapter AUS



Item No.
1.100160

Description
Single Plug Adapter AUS

Colour
white

EAN
7640167560073

Customs tariff code
8536.6990



Technical details:

Safety proofed:	IEC 60884, LVD EN 60950, DEKRA, UL
Input voltage:	110 - 250V
Max. load:	16A
Power rating:	100V - 1600W / 250V - 4000W
3 Pol:	Yes
Earthed:	Yes
USB Output:	No
USB protection:	Not necessary

Logistic details:

	length mm	width mm	high mm	gram
Product	58	58	45	75
PU Box 1	64	64	80	90
Master 20	330	140	185	1900
Pallet 4000	1200	800	1800	kg 380

INPUT

AUSTRALIA/CHINA




2-pole



3-pole

ITALY



3-pole

SWITZERLAND



3-pole

UK




2-pole




3-pole

USA



2-pole



3-pole

EUROPE



2-pole


OUTPUT

AUS



Plug type:

I



designed and engineered in Switzerland



Datasheet

Single Plug Adapter AUS with USB



Item No.	Description	Colour	EAN	Customs tariff code
1.100170	Single Plug Adapter AUS with USB	white	7640167560080	8536.6990



Technical details:


Safety proofed:	IEC 60884, LVD EN 60950, DEKRA, UL
Input voltage:	110 - 250V
Max. load:	16A
Power rating:	100V - 1600W / 250V - 4000W
3 Pol:	Yes
Earthed:	Yes
USB Output:	5V - 2.1Ah
USB protection:	Overload & short circuit

Logistic details:

	length mm	width mm	high mm	gram
Product	58	58	45	75
PU Box 1	64	64	80	103
Master 20	330	140	185	2200
Pallet 4000	1200	800	1800	kg 440

INPUT


AUSTRALIA/CHINA



2-pole

3-pole

ITALY



3-pole

SWITZERLAND



3-pole

UK




2-pole




3-pole

USA



2-pole



3-pole

EUROPE




2-pole

OUTPUT AUS WITH USB



Plug type: I



designed and engineered in Switzerland



Datasheet

Single Plug Adapter IT



Item No.
1.100180

Description
Single Plug Adapter IT

Colour
white

EAN
7640167560097

Customs tariff code
8536.6990



Technical details:

Safety proofed:	IEC 60884, LVD EN 60950, DEKRA, UL
Input voltage:	110 - 250V
Max. load:	16A
Power rating:	100V - 1600W / 250V - 4000W
3 Pol:	Yes
Earthed:	Yes
USB Output:	No
USB protection:	Not necessary

Logistic details:

	length mm	width mm	high mm	gram
Product	58	58	45	75
PU Box 1	64	64	80	90
Master 20	330	140	185	1900
Pallet 4000	1200	800	1800	kg 380

INPUT

AUSTRALIA/CHINA




2-pole



3-pole

ITALY



3-pole

SWITZERLAND



3-pole

UK




2-pole




3-pole

USA




2-pole



3-pole

EUROPE




2-pole

OUTPUT

IT



Plug type: **L**



designed and engineered in Switzerland



Datasheet

Single Plug Adapter IT with USB



Item No.
1.100190

Description
Single Plug Adapter IT with USB

Colour
white

EAN
7640167560103

Customs tariff code
8536.6990



INPUT

AUSTRALIA/CHINA




2-pole



3-pole

ITALY



3-pole

SWITZERLAND



3-pole

UK




2-pole




3-pole

USA



2-pole



3-pole

EUROPE



2-pole

Technical details:

Safety proofed:	IEC 60884, LVD EN 60950, DEKRA, UL
Input voltage:	110 - 250V
Max. load:	16A
Power rating:	100V - 1600W / 250V - 4000W
3 Pol:	Yes
Earthed:	Yes
USB Output:	5V - 2.1Ah
USB protection:	Overload & short circuit


Logistic details:

	length mm	width mm	high mm	gram
Product	58	58	45	75
PU				
Box 1	64	64	80	103
Master				
20	330	140	185	2200
Pallet				
4000	1200	800	1800	kg 440

OUTPUT IT WITH USB



Plug type: **L**



designed and engineered in Switzerland



Datasheet

Single Plug Adapter CH



Item No.
1.100200

Description
Single Plug Adapter CH

Colour
white

EAN
7640167560110

Customs tariff code
8536.6990



Technical details:

Safety proofed:	IEC 60884, LVD EN 60950, DEKRA, UL
Input voltage:	110 - 250V
Max. load:	16A
Power rating:	100V - 1600W / 250V - 4000W
3 Pol:	Yes
Earthed:	Yes
USB Output:	No
USB protection:	Not necessary

Logistic details:

	length mm	width mm	high mm	gram
Product	58	58	45	75
PU Box 1	64	64	80	90
Master 20	330	140	185	1900
Pallet 4000	1200	800	1800	kg 380

INPUT

AUSTRALIA/CHINA




2-pole



3-pole

ITALY



3-pole

SWITZERLAND



3-pole

UK




2-pole




3-pole

USA




2-pole



3-pole

EUROPE




2-pole

OUTPUT

CH



Plug type: **J**



designed and engineered in Switzerland



Datasheet

Single Plug Adapter CH with USB



Item No.	Description	Colour	EAN	Customs tariff code
1.100210	Single Plug Adapter CH with USB	white	7640167560127	8536.6990



Technical details:


Safety proofed:	IEC 60884, LVD EN 60950, DEKRA, UL
Input voltage:	110 - 250V
Max. load:	16A
Power rating:	100V - 1600W / 250V - 4000W
3 Pol:	Yes
Earthed:	Yes
USB Output:	5V - 2.1Ah
USB protection:	Overload & short circuit

Logistic details:


	length mm	width mm	high mm	gram
Product	58	58	45	75
PU Box 1	64	64	80	103
Master 20	330	140	185	2200
Pallet 4000	1200	800	1800	kg 440

INPUT

AUSTRALIA/CHINA




ITALY




SWITZERLAND



UK



USA




EUROPE



OUTPUT CH WITH USB



Plug type: **J**



designed and engineered in Switzerland