



ICY BOX IB-AC548

Mini DisplayPort™ to active HDMI® adapter

Key features

- Active HDMI® signal converter
- Adapts a Mini DisplayPort™ 1.2a to a HDMI® interface
- Resolution up to 3840x2160@60 Hz, 1080p 3D (120 Hz)
- Supports HDMI® specification 2.0, HDCP 1.4/2.2 and up to 6 Gbit/s per channel
- Supports up to 192 kHz audio frame rate and up to 24 Bit audio sample size
- Up to 8 channel LPCM, compressed audio (AC-3, DTS) and HBR audio formats
- Plug & Play - no software installation



Packing content
1x IB-AC548

High quality video output

The IB-AC548 Mini DisplayPort™ to HDMI® cable is designed to connect embedded DisplayPort™ devices (laptop, desktop PC etc.) to HDMI® embedded devices (television, monitor etc.). With the HDMI® and Mini DisplayPort™ 1.2a specifications, this adapter's video bandwidth can reach up to 18 Gbit/s total and the resolution is up to 3840x2160@60 Hz. Besides, no extra driver is needed when plugging into any supported device.

Technical data

Model	IB-AC548
Article no.	60232
EAN code	4250078165637
Brand	ICY BOX
Colour	Black
Chipset	Parade PS176
Material	Aluminium, PVC

Host interface	Mini DisplayPort™ 1.2a
Video output	High Speed HDMI®
Resolution	Up to 3840x2160@60 Hz
Cable length	300 cm
Power supply	Bus powered, 3.3 V
Supported OS	Windows, macOS

The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries.



ICY BOX **IB-AC548** Mini DisplayPort™ to active HDMI® adapter



Ingeniously adapted

This Adapter is future proof and delivers stunning 4K@60 Hz, 1080p in 3D (120 Hz), 4K Video Streaming (HDCP 2.2) and clear sound on 8 channels.



It's in the cable

Not every device is able to adapt a Mini DisplayPort™ to an HDMl® signal. No Problem, this task is fulfilled by the Parade PS176 chipset of the IB-AC548, therefore maximum compatibility is guaranteed. Devices that would fit the adapting task are also profiting from this chipset because the computing power intensive signal adapting is done by the active cable.



3 meter possibilities

The way from the laptop/PC to beamer/TV is not always easy and short. With the 3 meter cable you stay flexible and dont have to settle with uncomfortable positions.

Logistical data

Packing unit: 50 pcs./carton
Total weight: 13.0 kg/carton
Gross weight: (with packing): 0.239 kg
Net weight: 0.170 kg

Dimension/carton: 530x470x260 mm
Dimension (with packing): 200x100x45 mm
Dimension of article: 3000x25x13 mm
Country of origin: China

