



## ICY BOX IB-DK2102-C

### USB Type-C™ Docking Station with triple video output

#### Key features

- Premium aluminium enclosure
- Three video interfaces (HDMI®, Mini DP™ and VGA)
- Supports 4k@30 Hz resolution (single mode, HDMI® or mini DP™)
- Dual monitor function - connect two extended monitors at the same time (only Windows®)
- Three USB 3.0 Type-A interfaces, data transfer rate up to 5 Gbit/s
- One Type-C™ charge port for Power Delivery 2.0 up to 60 W (20 V@3 A)
- SD and microSD (UHS-I) card reader for most common card specifications
- 3.5 mm stereo combo jack (microphone in / audio out)
- Gigabit LAN RJ45 interface supports 10/100/1000 Mbit/s bandwidth



#### Packing content

IB-DK2102-C, 2x rubber pads, manual

#### Technical data

<b>Model</b>	IB-DK2102-C
<b>Article no.</b>	60389
<b>EAN</b>	4250078167129
<b>Brand</b>	ICY BOX
<b>Colour</b>	Anthracite / black
<b>Material</b>	Aluminium + plastic
<b>Chipset</b>	VL100, VL812, RLT8153, STDP4320
<b>Input interface</b>	USB Type-C™ to host computer, integrated cable, 15 cm
<b>Output interface</b>	1x High Speed HDMI® Type-A 3x USB 3.0 Type-A, 2x 5 V@0.9 A, 1x 5 V@1.5 A 1x Gigabit LAN RJ45 interface 1x SD & microSD card reader, SD 3.0 (UHS-I), Single LUN 1x Type-C™ charging port for Power Delivery 2.0 up to 60 W (20 V@3 A), no data transfer 1x 3.5 mm stereo combo jack (microphone in / audio out)
<b>Video resolution</b>	High Speed HDMI® up to 1x 3840x2160@30 Hz Mini DP™ up to 3840x2160@30 Hz VGA up to 1920x1200@60 Hz

#### Transfer rate

#### Power supply Power Delivery Operating system System requirements

USB 3.0: up to 5 Gbit/s, UASP supported  
LAN: up to 10/100/1000 Mbit/s  
Bus powered  
Supports up to 60 W from original power supply of the computer  
Windows® 10, macOS®

- USB Type-C™ enabled Windows® / macOS® computer, no MST support for macOS® computer (dual output only mirroring)
- DisplayPort™ Alt Mode and Power Delivery 2.0 support required!
- The device is compatible with Thunderbolt™ 3 equipped computers
- Dual video output: mini DP™ + HDMI® or mini DP™ + VGA synchronous display (2x 1920x1080@60 Hz)
- No power supply included (only necessary for Power Delivery)

DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. The terms HDMI® and HDMI® High-Definition Multimedia Interface, and the HDMI® logo are trademarks or registered trademarks of HDMI® LA, Inc. in the United States and other countries.

**ICY BOX®**[www.raidsonic.de](http://www.raidsonic.de)

## ICY BOX **IB-DK2102-C**

### USB Type-C™ DockingStation with triple video output



#### Connection desires

Notebooks and other mobile computers are getting ever smaller but this comes at the expense of connectivity. The DockingStation IB-DK2102-C can permanently alleviate the lack of connection. 3x USB 3.0, 1x Gigabit LAN, 1x DisplayPort™, 1x HDMI®, 1x VGA, 1x USB Type-C™ PD 2.0, 1x SD & microSD card reader and a headphone combo jack are provided.



#### Always informed

Three different video interfaces are available, where two monitors can be operated at the same time. They enables you to connect a Mini DP and HDMI® or Mini DP and VGA device simultaneously.



#### The perfect position

The perfect symbiosis of stylish appearance, the latest technology and compact size. The high-grade aluminium housing not only looks good, but also offers comfortable accessibility to the most important expansion ports and, thanks to its shape, at the same time can serve as a riser for the notebook.

#### Logistical data

**Packing unit:** 20 pcs./carton  
**Total weight:** 8.50 kg/carton  
**Gross weight (with packing):** 0.37 kg  
**Net weight:** 0.25 kg

**Dimension/carton:** 420x280x300 mm  
**Dimension (with packing):** 25x130x340 mm  
**Dimension of article:** 80x280x18 mm  
**Country of origin:** China

