



ICY BOX IB-DK4034-CPD

USB Type-C[™] notebook DockingStation

Key features

- Input (to notebook / PC): USB 3.0 Type-C™
- Output: 1x High Speed HDMI® Type-A (up to 3840x2160@30 Hz)
 2x USB 3.0 Type-A (USB 3.0 downward compatible to USB 2.0)
 1x Ethernet RJ45, 1x SD card reader (tested up to 128 GB)
 1x USB Type-C™ with Power Delivery (PD) function (max. 20 V@3 A)
- Mirroring and extending of the notebook display via HDMI®
- Bus powered, no power supply necessary

Note: Only pass through from downstream USB Type- $C^{\mathbb{N}}$ to upstream for connecting the Type- $C^{\mathbb{N}}$ power supply of the notebook in use.



Packing content

1x IB-DK4034-CPD, 1x quick installation guide

Notebook DockingStation

The USB Type-C[™] notebook DockingStation is designed for extra connectivity demands of a notebooks or other computers. With the DockingStation, you can extend the USB Type-C[™] connection of a computer to one more HDMI[®] display, Ethernet network, USB peripherals, SD cards and Power Delivery (PD) function via the USB Type-C[™] interface.

Technical data

 Model
 IB-DK4034-CPD

 Article no.
 60213

 EAN / GTIN code
 4250078165521

 Brand
 ICY BOX

 Colour
 Silver/white

 Material
 Aluminium + PC + A

 Material
 Aluminium + PC + ABS

 Chipset
 VL100, VL813, PS176, RTL8153

Input interface USB Type- C^{IM} (UFP) from host PC, USB Type- C^{IM} (DFP) to host PC

(only for PC power delivery up to 20 V@3 A)

 $\textbf{Output interface} \hspace{15mm} 1x \hspace{1mm} \textbf{High Speed HDMI}^{\circledcirc}, \hspace{1mm} 2x \hspace{1mm} \textbf{USB 3.0 Type-A (DFP)}, \hspace{1mm} 1x \hspace{1mm} \textbf{Ethernet RJ45},$

1x SD card reader, 1 x USB Type-C[™] only with PD function

USB 3.0 speed Up to 5 Gbit/s

HDMI Up to 3840x2160@30 Hz **Power supply** Bus powered via USB Type-C[™] port

 Operating system
 Windows® 10 and above

 System requirements
 macOS® 10.11.x and above, PC with USB Type-C™ interface suppor

ting DisplayPort™ Alt Mode








ICY BOX IB-DK4034-CPD

USB Type-C[™] notebook DockingStation



A bit of everything

With a USB Type- C^{∞} host, the door is opened for five additional ports, 1x Gigabit Ethernet, 1x SD cardreader, 1x HDMI $^{\odot}$ and 2x USB 3.0 Type-A are opened. In addition, mobile devices can be charged when the appropriate power supply is connected.



A bit of input

USB Type- C^{M} is the new standard for PCs, notebooks, tablets and the like. The high data transfer rate of the USB 3.0 protocol of up to 5 Gbit/s serves this adapter very well.



Slim and elegant

Due to the low height, the IB-DK4034-CPD is very handy as well as flexible for many situations. With the integrated USB Type- C^{∞} cable you can always get a connection with the latest PCs, laptops or mobile devices.

Logistical data

 Packing unit:
 50 pcs./carton

 Total weight:
 8,6 kg/carton

 Gross weight: (with packing):
 0.161 kg

 Net weight:
 0.085 kg

Dimension/carton:
Dimension (with packing):
Dimension of article:
Country of origin:

420x280x335 mm 200x100x25 mm 117x46x16 mm







RaidSonic Technology GmbH • Kurt-Fischer-Straße 50 • 22926 Ahrensburg / Germany
Telephone: +49-(0)4102 – 468 900 (Sales) • Fax: +49-(0)4102 – 468 901 • info@raidsonic.de • www.raidsonic.de
Offers and deliveries are only done under our General Terms and Conditions. Errors and omissions excepted.

