



ICY BOX IB-HUB1411-QC3 4 port USB 3.0 Hub with 2 charging ports

Key features

- 4 port USB 3.0 Type-A hub
- 1x QC 3.0 charging port, 1x fast charging port
- Flexible mounting options with the desktop or wallmount bracket
- \bullet Incl. 12 V / 4 A power adapter and USB 3.0 cable to hostcomputer
- Transfer rate up to 5 Gbit/s
- Aluminium case
- Plug & Play



Packing content

1x IB-HUB1411-QC3, 1x USB 3.0 Type-B to Type-A cable, 710 mm length, 1x power adapter, 1x quick installation guide

Attached to help

The IB-HUB 1411-U3 is specially adapted to compete in industrial environments. The high-grade aluminium housing can withstand a lot and ensures effective heat dissipation. Thanks to the mounting brackets, it can be mounted and used almost everywhere. In addition to the four USB 3.0 ports, it offers one fast charge port and one QC 3.0 charging port. These ports are available even if the IB-HUB 1703-U3 is not connected to a hostcomputer. The hub can be switched off if desired.

Technical data

Colour

 Model
 IB-HUB1411-QC3

 Article no.
 60363

EAN code 4250078166856 **Brand** ICY BOX

MaterialAluminiumInterface to hostcomputer1x USB 3.0 Type-AInterface to devices4x USB 3.0 Type-A

Black

1x QC 3.0 charging port: max. 18 W 1x fast charge port: max. 12 W for single port, complies with the battery charging

specification (BC 1.2)

 $\textbf{Charging spezification} \quad \text{USB 3.0: 5 V / 0.9 A, max. 4.5 W}$

QC 3.0: 3.6 - 12 V / 0 - 3 A, max. 18 W USB-BC 1.2: 5 V / 2.4 A, max. 12 W

Total output: 12 V / 4 A, max. 48 W VL817

Chipset VL81
Plug & Play Yes
Power switch Yes

Transfer rate Up to 5 Gbit/s **LED** Power

Power adapter Input: 100-240 V
Output: 12 V / 4 A

Operating system Windows® and macOS®







ICY BOX **IB-HUB1411-QC3**4 port USB 3.0 Hub with 2 charging ports



Charging

The QC 3.0 charge port with up to 12 V offers an extremely fast and convenient way to charge compatible smartphones, tablets, digital cameras and power banks. The fast-charge port (5 V / 2.4 A) complies with the new battery charging specification (BC 1.2) and completes the portfolio of ports. Thanks to the power supply unit, this is also possible without a connected host computer. The hub can be switched off via button.



Fourfold

Four USB 3.0 ports in one sweep. If all USB 3.0 ports are busy again, the phone needs to be charged and important data must be copied spontaneously back and forth from external storage devices, this candidate can help.



Mounted

Every working environment is different. The IB-HUB1411-QC3 faces this challenge and offers all features to compete in both private and industrial environments. Thanks to the table or wall mounting bracket, the high-grade aluminium housing can be installed stably.

Logistical data

 Packing unit:
 15 pcs./carton

 Total weight:
 10.4 kg/carton

 Gross weight: (with packing):
 0.635 kg

 Net weight:
 0.170 kg

Dimension/carton: 42
Dimension (with packing): 20
Dimension of article: 14
Country of origin: Ch

423x333x243 mm 200x100x80 mm 140x65x30 mm







RaidSonic Technology GmbH • Kurt-Fischer-Straße 50 • 22926 Ahrensburg / Germany
Telephone: +49-(0)4102 – 468 900 (Sales) • Fax: +49-(0)4102 – 468 901 • info@raidsonic.de • www.raidsonic.de
Offers and deliveries are only done under our General Terms and Conditions. Errors and omissions excepted.

