

W 250 S

Art. No. 9034 – 4 Ω

Art. No. 9035 – 8 Ω



Technische Daten / Technical Data

Nennbelastbarkeit	
Rated power	100 W
Musikbelastbarkeit	
Maximum power	150 W
Impedanz	
Impedance	4 Ω / 8 Ω
Übertragungsbereich (–10 dB)	
Frequency response (–10 dB)	fu–5500 Hz
Mittlerer Schalldruckpegel	
Mean sound pressure level	90 dB (1 W/1 m)
Grenzauslenkung x_{mech}	
Excursion limit x_{mech}	± 7 mm
Resonanzfrequenz	
Resonant frequency	33 Hz / 31 Hz
Obere Polplattenhöhe	
Height of front pole-plate	7 mm
Schwingspulendurchmesser	
Voice coil diameter	38 mm Ø
Wickelhöhe	
Height of winding	17 mm
Schallwandöffnung	
Cut-out diameter	233 mm Ø
Gewicht netto	
Net weight	3,0 kg

Weitere Daten Seiten / for further data see pages 274–275

fu: Untere Grenzfrequenz abhängig vom Gehäuse; Lower cut-off frequency depending on cabinet

25 cm (10") HiFi-Tieftöner mit starkem Antrieb, tiefgezogener Polplatte und 38-mm-Schwingspule für hohe Belastbarkeit. Elastische Gummisicke, beschichtete Papiermembran und Druckausgleichsöffnung in der Membran.

Bestückung: FIESTA 25

25 cm (10") HiFi woofer with strong drive, extended rear pole plate and 38 mm voice-coil for high power handling. Elastic rubber surround, coated paper cone and magnet vent.

Applied to: FIESTA 25

Volumen/Prinzip; Volume/Principle	BR-Rohr; BR-Channel	f_b
50 l/Bassreflex; bass reflex	2 x BR 15.34	43 Hz
70 l/Bassreflex; bass reflex	2 x BR 15.34	39 Hz
	1 x BR 25.50 (Länge; length 7 cm)	
100 l/Bassreflex; bass reflex	2 x BR 15.34 (Länge; length 10 cm)	34 Hz

