SAFETY DATA SHEET PAGE 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: TURBO OIL PRF 290 Approval date: 23.3.2000

Supplier: TAEROSOL Oy

Aakkulantie 21, FIN-36220 Kangasala Finland Tel: +358 3 356 5600 Fax: +358 3 356 5656

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients considered hazardous to health:

CAS-number	Chemical name	Concentration
64742-49-0	Hydrocarbon solvents	30-50 %
68476-49-3	Propane	10-20%
68476-40-4	Butane	10-20 %
64742-65-0	Mineral Oil	10-20 %
64742-62-7		

3. HAZARDS IDENTIFICATION

Extremely flammable. Hydrocarbon solvents vaporize easily. Very big concentrations in the air may effect headache, daze and indisposition.

4. FIRST AID MEASURES

Eye contact: Flush thoroughly with water. If irritation continues, call a doctor.

Skin contact: Wash contact areas with soap and water. If irritation continues, call a doctor. Polluted clothes may be flammable, they must be moisten before taking off. Clothes must be washed before used again.

Inhalation: If unusual tiredness and queasiness occurs when breathing big concentrations, go to fresh air. If continuing, call a doctor.

Ingestion: When taken internally, rinse with water. DO NOT VOMIT, contact doctor. If the patient has no queasiness, give 1 to 2 spoons cream. Ingestion may cause pneumonia.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide, foam, powder and sand for small fires.

Special fire fighting procedures: Risk of explosion if the cans overheat in fire and the pressure rises.

SAFETY DATA SHEET PAGE 2

Special protective equipment: Normal protective equipment.

Other recommendations: Do not extinguish with water-jet.

6. ACCIDENTAL RELEASE MEASURES

Notification procedures: Dispose material according to current applicable laws and regulations.

Procedures if material is released or spilled: -

Environmental precautions: Prevent spills from entering to groundwater.

Personal precautions: Evacuate all unnecessary people.

7. HANDLING AND STORAGE

Handling: Breathing the vapours and continuos or long-term contacts to skin must be avoided. Keep away from sources of ignition. No smoking. Keep away from children.

Storage: In storage appropriate for extremely flammable aerosols.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: Adequate ventilation is recommended.

Respiratory protection:-

Eye protection: Normal industrial eye protection practices should be employed.

Skin protection: All contacts to skin must be avoided. If necessary use PVC-gloves.

Exposure limits:-

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and odour: Clear, colourless liquid

Boiling point: 50 °C (Hydrocarbon solvents), -20 °C (Prop./But.)

Melting point:

Flash point: $< 0^{\circ}$ C

Auto flammability: 245 °C

SAFETY DATA SHEET PAGE 3

Density: 750 Kg/m³

Vapour pressure:

Viscosity at 40 °C: 20 - 100 mm²/s (after hydrocarbon solvents have volatile)

Solubility in water: Insoluble

10. STABILITY AND REACTIVITY

11. TOXICOLOGICAL DATA

Inhalation:-

Eye irritation: Irritates slightly eyes.

Skin irritation: Irritates slightly skin.

Other acute toxicity: Low toxicity.

12. ECOLOGICAL INFORMATION

Environmental fate and effects: -

13. DISPOSAL CONSIDERATIONS

Waste disposal: Empty cans must be disposed according to laws and environment officials.

RCRA Information:-

14. TRANSPORT INFORMATION

UN-Number: 1950

ICAO/IATA: 2.1

RID/ADR: 2, 5F (ADR)

IMDG: 2.1

EmS No 2-13

MFAG No 620

SAFETY DATA SHEET PAGE 4

15. REGULATORY INFORMATION

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding +50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition. No smoking. Keep away from children. F+ Extremely flammable

16. OTHER INFORMATION
