KÖNIG ELECTRONIC

Your World, Our Technology

SOUND & LIGHT

Active Studio Monitor Set

4” Aramid Kevlar woofer

USPs:

- Bi-amplified
- 4" Aramid Kevlar woofer
- 1" ferro-fluid silk dome tweeter

General Information:

This active studio monitor set has a perfect response with a very natural and transparent sound. The speakers are bi-amplified and have an integrated electronic cross-over for a better Signal to Noise Ratio and lower Total Harmonic and Intermodulation Distortion. These magnetic shielded monitors are professionally designed and equipped with a 4” Aramid Kevlar woofer and a 1" ferro-fluid silk dome tweeter. The round shaped corners and bass-reflex ports ensure a better sound projection.

Specifications:

• Frequency range:	66 Hz–20 kHz
• Rated output power:	2x 60 W Peak 2x 15 W RMS
• Crossover frequency:	3 kHz
• High-pass filter:	35 Hz
• Low-pass filter:	-
• LF driver:	4” Aramid Kevlar
• HF driver:	1” Soft dome
• Input connections:	RCA, 6.3mm Jack
• Level controls:	Volume, Treble, Bass
• Enclosure:	Bass-reflex
• Protection:	Overload
• Power requirements:	230 V AC/50-60 Hz
• Dimensions:	168x240x180
• Weight per set:	6.5 kg

Manual

Sales Information:

Order code:	PA-STMON40
TARIC code:	8518220090
Description:	Active Studio Monitor Set
Packaging:	Giftbox
Going price:	€ 199.00

5 412810 123728

Quantity:	LxWxH (mm)	Weight
1 pc	447 x 243 x 312	8140 gr.

©2009 König®. All rights reserved. König® is a registered trademark.
Specifications are subject to modification without prior notice. Contents may differ slightly from what is shown.
König can not be held responsible, nor liable for the information contained in this document.