


# Blade receptable

Blade Receptacles, Fully Insulated, RND



## SPECIFICATION:

Material	Brass
Surface material	Tin-plated

## PRODUCT RANGE:

Art. Nr.	Contact	Cross-section	Colour	Insulation material	Temperature range	Voltage	Thickness
RND 465-00005	2.8 x 0.8 mm	0.5...1.5 mm <sup>2</sup>	red	Nylon	max. +105 °C	600 V	0.3 mm
RND 465-00006	6.3 x 0.8 mm	4...6 mm <sup>2</sup>	yellow	Nylon	max. +105 °C	600 V	0.4 mm
RND 465-00046	2.8 x 0.5 mm	0.5...1.5 mm <sup>2</sup>	red	Nylon	max. +105 °C	600 V	0.3 mm
RND 465-00073	4.8 x 0.8 mm	0.5...1.5 mm <sup>2</sup>	red	Nylon	max. +105 °C	600 V	0.35 mm
RND 465-00074	6.3 x 0.8 mm	0.5...1.5 mm <sup>2</sup>	red	Nylon	max. +105 °C	600 V	0.4 mm
RND 465-00075	4.8 x 0.8 mm	1.5...2.5 mm <sup>2</sup>	blue	Nylon	max. +105 °C	600 V	0.35 mm
RND 465-00076	6.3 x 0.8 mm	1.5...2.5 mm <sup>2</sup>	blue	Nylon	max. +105 °C	600 V	0.4 mm