

## UNIX 100, LTE 700, Ch 21-48 (Color box)

Art. Number 105570



### TRIAX UHF LTE 700 Aerials

Disruption free installation from rooftop to outlet.

- Interference protection from LTE 700 & 800 signals
- Quick and easy installation with semi-assembled aerials
- Mechanical filtering for higher gain
- Reliable high-quality aerials secures end-consumer satisfaction
- Corrosion and weather proof dipole housing
- Designed to receive DTT signals in the 470...694 MHz range
- Access to reliable, expert support from TRIAX

## Technical Specifications

### ORDER INFORMATION

EAN Number 5702661055706

### FREQUENCY RANGE

Band UHF  
Channels 21...48  
Frequency range UHF | MHz 470...694 MHz  
LTE protection @ 700Mhz

### GAIN

Gain | dBi 17 max dBi  
Gain @ 474 MHz (Ch. 21) | dBi 13.3 dBi

### LOSS

Rejection @ 788 MHz (Ch. 60) | dB 14.6 dB

### ELECTRICAL

Front to back ratio - horizontal | dB 20 dB

### MECHANICAL



# TRIAx

connecting the future

## Technical Specifications

Elements	80
Windload @42 m/s   N	162 N
Beamwidth horizontal   °	±15 °
Bracketry	Mast Support Boom
Main material	Aluminium
Packing QTY	1
Product Length   mm	2343 mm
Product Width   mm	580 mm
Packaging Height   m	0.100 m
Packaging Width   m	0.455 m
Packaging Depth   m	1.045 m
Packaging Volume   m3	0.048 m3
Net Weight   kg	2.300 kg
Tara Weight   kg	0.850 kg
Total Weight   kg	3.150 kg