Art. No. 50318 – schwarz/*black* **Art. No. 50316** – weiß/*white* **WB 16**

2-Wege-Kompaktbox mit stabilem Kunststoffgehäuse (weiß/schwarz), bestückt mit einem 16-cm-Tieftöner und einem Hochtöner für einen breiten Übertragungsbereich. Gut geeignet für Musik- und Sprachwiedergabe. Universell einsetzbar für professionelle Beschallungen oder im Heimbereich. Sowohl 100-V-Betrieb durch integrierten Übertrager als auch 8-Ohm-Betrieb möglich. Auswahl der Leistungsanpassungen des 100-V-Übertragers sowie der Betriebsart 8 Ohm mittels Drehschalter. Drehbarer Montagebügel zur flexiblen Montage (waagerecht oder senkrecht), zusätzlich ins Gehäuse eingelassene Gewinde zur Montage einer Halterung (z.B. Gelenk).

Kunststoff: ABS (UL 94:HB)

2-way compact speakers *in a sturdy plastic housing (white), fitted with one 16 cm woofer and one tweeter providing broad frequency response. Well suited for music and voices. Universally applicable to professional PA or in the home. Can be run as a 100 V system or as 8 ohm units due to an integrated transformer. 100 V transformer and 8 ohm mode are selected using a knob. Swivelling fixing bracket allows the speakers to be mounted horizontally or vertically, as required, and the housing is equipped with a threaded hole for attaching to a bracket or swivelling arm.*

Plastic: ABS (UL 94:HB)



+70 °C
–25 °C

.txt-Download

Wasserfest
Water-proof

Schutzart / *Protective system* (IP) IP 54









		WB 16
Nenn- / Musikbelastbarkeit	*Rated / Maximum Power*	60 W / 90 W
Trafoanpassung / Impedanz	*Transformer matching / Impedance*	25; 15; 7,5; 4; 2 W / 8 Ω
Schalldruckpegel	*Sound pressure level*	92 dB (1 W/1 m) @ 16223 Hz
Abstrahlwinkel (–6 dB)	*Opening angle (–6 dB)*	52° / 4000 Hz hor.; 97° / 4000 Hz vert.
Übertragungsbereich (–10 dB)	*Frequency response (–10 dB)*	80–20000Hz
Mittlerer Schalldruckpegel	*Mean sound pressure level*	89 dB (1 W/1 m)
Max. Schalldruckpegel	*Max. sound pressure level*	103 dB (25 W/1 m)
Resonanzfrequenz	*Resonance frequency*	–
Schwingspulendurchmesser	*Voice coil diameter*	–
Schallwandöffnung	*Cutout diameter*	–
Gewicht netto	*Net weight*	2,8 kg