

Weller®

WX 2 Control Unit


NEW


WX 2 control unit

Technical Data WX 2

Dimensions

L x B x H (mm) 170 x 151 x 130
L x B x H (inch) 6,69 x 5,94 x 5,12

Weight

ca. 3,2 kg

Mains voltage

230 V, 50 Hz

Power input

200 W (240 W)

Protection class

I, case antistatic

Protection

Mains fuse T2 A

Temperature range

adjustable 50° C – 550° C
(150° F – 999° F)

Adjustable temperature range depends of tools.

Temperature accuracy

± 9° C (± 17° F)

Temperature stability

± 2° C (± 4° F)

Equipotential bonding

3,5 mm jack socket on the back of the unit

Material case

Aluminium base with antistatic, black coating, antistatic plastic case

Capacitive touch-screen

6 touch keys, turn-and-klick wheel with enter key and finger guide, patented glass capacitive touch screen with antistatic, chemical and temperature resistant coating.

Display

Back lit LC-Display

Order No.

T0053420699



Intuitive use



Multiple language menu navigation



Multi-purpose USB port



WX tool connection



Fume extractions

Fume extractions solutions

The Weller® Zero-Smog® systems put an end to pollution from soldering fumes or vapours from adhesives. The Zero-Smog® systems can be connected directly using the WX port and controlled via the WX display.

Order No.

- T0053626671 WFE 2S with automatic pressure control
Portable fume extraction for volume extraction with built-in turbine and automatic pressure control for constant air flow
- T0053626699 WFE 2S
Portable fume extraction for volume extraction with built-in turbine
- T0053649699 WFE 4S
Mobile fume extraction for volume extraction with built-in turbine
- T0053658699 WFE 8S
Mobile fume extraction for volume extraction with built-in pre-filter for solder machines
- T0053647699 WFE 20D
Fume extraction for tip extraction applications with built-in turbine



Vorheizplatten

Heating plates

The Weller® heating plates are used to preheat electronic components and can be connected directly using the WX port and controlled via the WX display.

Order No.

- T0053364899 WHP 1000
heating plate 1000 W/230 V,
heating surface: 220 x 150 mm (heat)
- T0053338699 WHP 3000
Infrared heating plate, 600 W/230 V,
with easy fix board holder,
heating surface: 120 x 190 mm (heat)
- T0053364699 WHP 3000
Infrared heating plate, 1200 W/230 V,
with easy fix board holder,
heating surface: 190 x 245 mm (heat)

Cooper Tools GmbH

A company of Apex Tool Group, LLC.
Carl-Benz-Straße 2
74354 Besigheim, Germany
Tel.: +49 (0) 7143 580-0
Fax: +49 (0) 7143 580-108
www.weller.eu