PCB Terminal Blocks

10 mm Pitch, Low Profile



2-12 pole interlocking terminal block with pin spacing of 10mm for high voltage operation

Guided pin alignment
Pin/terminal - Tin plated brass
Wire clamp - Nickel plated brass
Screw/torque - M2.5 steel Ni plated
Recommended PCB hole size - ø1.4mm

SPECIFICATION:

Pitch	10 mm
Termination type	Clamp Terminals/Screw Connection
Connection direction	horizontal
Rated current to EN	10 A
Rated current to UL	10 A
Rated voltage to EN	300 V
Rated voltage to UL	300 V
Connection cross-section	0.13-1.31 mm² (26-16 AWG)
Colour	green
Test voltage	2 kV
Temperature range	-33...+120 °C
Width	8.45 mm
Height	10 mm
Material	PA 66, UL94-V0

PRODUCT RANGE:

Art. Nr.	Poles	Length
RND 205-00298	2	15 mm
RND 205-00299	3	25 mm
RND 205-00300	4	35 mm
RND 205-00301	5	45 mm
RND 205-00302	6	55 mm
RND 205-00303	7	65 mm
RND 205-00304	8	75 mm
RND 205-00305	9	85 mm
RND 205-00306	10	95 mm
RND 205-00307	11	105.0 mm
RND 205-00308	12	115 mm