

75060 V + 275 (0.6/3.7 + 2 x 0,75 mm²)

CCTV VIDEO-SYSTEMCABLE 75 Ohm

Cable for instance for networks of close-circuit video monitoring systems + power supply 12/24 V low voltage.

- single shielded
- copper bare braid wire
- good attenuation
- Made in Germany
- fulfilled RoHS (EN 2002/95 EG)



Building:	
Inner conductor	0,6 mm copper
Insulation	3,7 mm PE. +/- 0,1
Outer conductor	
a)	Copper braid bare wires
b)	
c)	
d)	
Jacket	12,6 x 6,1mm PVC black +/- 0,3
Electrical properties:	
Impedance	75 Ohm +/- 3
Capacity (pF/m)	67
Velocity (v/c)	0,66
Attenuation at 20°C (dB 100m)	
	1 MHz - 1,1
	5 MHz - 2,5
	10 MHz - 3,5
H05Z - K 2 x 0,75 mm ² red + black	
Return loss(dB)	-
Coupling resistance (mOhm/m)	-
Direct current resistance (Ohm/km)	Inner conductor: 63 Outer conductor: 13
Mechanical properties:	
Minimum bending radius	50 mm
Cable weight kg/km	+/- 98,5
Copper weight kg/km	+/- 38