

VC920 / VC980 操作說明

VC920Mini DisplayPort 轉 VGA 轉接器

VC980Mini DisplayPort 轉 HDMI 轉接器

VC920



VC980



操作說明

1. 將 VC920 / VC980 上的 Mini DisplayPort 接頭連接到 Mini DisplayPort 來源裝置
2. (a) 再用一條 VGA 線材將 VC920 連接至 VGA 顯示裝置
(b) 再用一條 HDMI 線材將 VC980 連接至 HDMI 顯示裝置

BSMI



D33866
RoHS

設備名稱: Mini DisplayPort 轉 VGA 轉接器/Mini DisplayPort 轉 HDMI 轉接器 型號 (型式) : VC920/VC980
Equipment name Type designation (Type)

單元 Unit	限用物質及其化學符號 Restricted substances and its chemical symbols					
	鉛 Lead (Pb)	汞 Mercury (Hg)	鎘 Cadmium (Cd)	六價鉻 Hexavalent chromium (Cr^{+6})	多溴聯苯 Polybrominated biphenyls (PBB)	多溴二苯醚 Polybrominated diphenyl ethers (PBDE)
電纜線 Cable	—	○	○	○	○	○
印刷電路部 件 PCBA	—	○	○	○	○	○
塑膠/其他 部件 Plastic /Others parts	○	○	○	○	○	○
金屬部件 Metal parts	—	○	○	○	○	○

備考1. “超出0.1 wt %” 及 “超出0.01 wt %” 係指限用物質之百分比含量超出百分比含量基準值。
Note 1 : “Exceeding 0.1 wt %” and “exceeding 0.01 wt %” indicate that the percentage content of the restricted substance exceeds the reference percentage value of presence condition.

備考2. “○” 係指該項限用物質之百分比含量未超出百分比含量基準值。
Note 2 : “○” indicates that the percentage content of the restricted substance does not exceed the percentage of reference value of presence.

備考3. “—” 係指該項限用物質為排除項目。
Note 3 : The “—” indicates that the restricted substance corresponds to the exemption.

代理商：宏正自動科技股份有限公司

地址：新北市汐止區大同路二段 125 號三樓

- 最大額定電壓: 3.3Vdc, 0.5A
- 最大操作環境溫度: 50°C